

## Variable rake guillotine shear

# 00750185

### HBX-S Series - HBX 2500-100S

The **HM Machinery HBX-S Series** represents the next generation of hydraulic sheet shears — designed for professionals who demand uncompromising accuracy, durability, and ease of operation.

Built on a solid welded steel frame for maximum rigidity and minimal vibration, the HBX-S ensures clean, precise cuts every time, even under heavy workloads.

Each model in the series is equipped with a **CNC motorized back gauge (1000 mm)** for quick and accurate positioning, while the **CNC-controlled blade gap, CNC-controlled rake angle, and CNC-controlled cutting length (stroke)** allow the operator to fine-tune every parameter to match material thickness and cutting requirements perfectly.

The result is optimal cutting quality, reduced material distortion, and longer blade life.

At the heart of the HBX-S Series is the **Cybelelec CybTouch 8 EasyCut** control system – a modern, intuitive touch-screen CNC interface that simplifies operation and setup.

The user-friendly design ensures fast programming, real-time feedback, and easy access to stored cutting programs, helping operators save time and boost productivity.

To ensure the highest level of reliability, the HBX-S Series is built using premium components, including **Schneider components** and a **Bosch Rexroth hydraulic system** – both globally recognized for their precision, safety, and long-term performance.

The HBX-S Series delivers consistent, high-quality results with every cut. It's the ideal choice for manufacturers seeking a dependable, high-performance shear that combines modern CNC technology with the trusted quality of **HM Machinery**.

**Experience ultimate control, superior cutting consistency, and long-lasting performance - with the HBX-S Series.**

#### Product Link:

<https://hmmachinery.bigleap.tech/en/product/variable-rake-guillotine-shear-837>

## Product Specification

Capacity (mm)	2550 x 10,0
Sheet thickness steel (mm)	10,0
Sheet thickness stainless (mm)	5,0
Cutting angle	0,5° - 2,0°
Cutting/min.	15
Back gauge (mm) tre	1000
Motorised back gauge	1
Table height (mm)	800
Motor (kW)	11
Voltage	3x400V - 50Hz
Tank capacity (L)	207
Length (mm)	3400
Width (mm)	1750
Height (mm)	1950
Net weight (kg)	7100

### Product Link:

<https://hmmachinery.bigleap.tech/en/product/variable-rake-guillotine-shear-837>