

## Variable rake guillotine shear

# 00750195

### HBX-S Series - HBX 3100-160S

The **HM Machinery HBX-S Series** represents the next generation of hydraulic sheet shears — designed for professionals who demand uncompromising accuracy, durability, and ease of operation.

Built on a solid welded steel frame for maximum rigidity and minimal vibration, the HBX-S ensures clean, precise cuts every time, even under heavy workloads.

Each model in the series is equipped with a **CNC motorized back gauge (1000 mm)** for quick and accurate positioning, while the **CNC-controlled blade gap, CNC-controlled rake angle, and CNC-controlled cutting length (stroke)** allow the operator to fine-tune every parameter to match material thickness and cutting requirements perfectly.

The result is optimal cutting quality, reduced material distortion, and longer blade life.

At the heart of the HBX-S Series is the **CybeleC CybTouch 8 EasyCut** control system – a modern, intuitive touch-screen CNC interface that simplifies operation and setup.

The user-friendly design ensures fast programming, real-time feedback, and easy access to stored cutting programs, helping operators save time and boost productivity.

To ensure the highest level of reliability, the HBX-S Series is built using premium components, including **Schneider components** and a **Bosch Rexroth hydraulic system** – both globally recognized for their precision, safety, and long-term performance.

The HBX-S Series delivers consistent, high-quality results with every cut. It's the ideal choice for manufacturers seeking a dependable, high-performance shear that combines modern CNC technology with the trusted quality of **HM Machinery**.

**Experience ultimate control, superior cutting consistency, and long-lasting performance - with the HBX-S Series.**

#### Product Link:

<https://hmmachinery.bigleap.tech/en/product/variable-rake-guillotine-shear-849>

## Product Specification

Capacity (mm)	3050 x 13,0
Sheet thickness steel (mm)	16,0
Sheet thickness stainless (mm)	6,5
Cutting angle	0,5° - 3,0°
Cutting/min.	8
Back gauge (mm) tre	1000
Motorised back gauge	1
Table height (mm)	850
Motor (kW)	22
Voltage	3x400V - 50Hz
Tank capacity (L)	290
Length (mm)	4000
Width (mm)	2150
Height (mm)	2300
Net weight (kg)	12000

### Product Link:

<https://hmmachinery.bigleap.tech/en/product/variable-rake-guillotine-shear-849>